Amendments to the Claims

1	1. (currently amended) A three-dimensional television system, comprising:
2	an acquisition stage, comprising:
3	a plurality of video cameras, each video camera configured to
4	acquire a video of a dynamically changing scene in real-
5	time;
6	means for synchronizing the plurality of video cameras; and
7	a plurality of producer modules connected to the plurality of
8	video cameras, the producers producer modules
9	configured to compress the videos to compressed videos
10	and to determine viewing parameters of the plurality of
11	video cameras;
12	a display stage, comprising:
13	a plurality of decoder modules configured to decompress the
14	compressed videos to uncompressed videos;
15	a plurality of consumer modules configured to generate a
16	plurality of output videos from the decompressed videos;
17	a controller configured to broadcast the viewing parameters to
18	the plurality of decoder modules and the plurality of
19	consumer modules;
20	a three-dimensional display unit configured to concurrently
21	display the <u>plurality of</u> output videos <u>onto a single</u>
22	display surface according to the viewing parameters; and

means of for connecting the plurality of decoder modules, the 23 24 plurality of consumer modules, and the plurality of 25 display units three-dimensional display unit; and 26 a transmission stage, connecting the acquisition stage to the display 27 stage, configured to transport the plurality of compressed videos and the 28 viewing parameters. 2. (currently amended) The system of claim 1, further comprising a plurality 1 of cameras to acquire calibration images displayed on the display surface of 2 3 the three-dimensional display unit to determine the viewing parameters. 3. (original) The system of claim 1, in which the display units are projectors. 1 4. (original) The system of claim 1, in which the display units are organic 1 2 light emitting diodes. 1 5. (original) The system of claim 1, in which the three-dimensional display 2 unit uses front-projection. 6. (original) The system of claim 1, in which the three-dimensional display 1 2 unit uses rear-projection. 1 7. (original) The system of claim 1, in which the display unit uses two-2 dimensional display element.

- 8. (currently amended) The system of claim 1, in which the display unit is
- 2 <u>uses a flexible fabric</u>, and further comprising passive display elements.
- 9. (currently amended) The system of claim 1, in which the display unit is
- 2 <u>uses a flexible fabric</u>, and further comprising active display elements.
- 1 10. (original) The system of claim 1, in which different output images are
- 2 displayed depending on a viewing direction of a viewer.
- 1 11. (currently amended) The system of claim 1, in which static view-
- 2 dependent images of an environment are displayed such that a display
- 3 surface of the display unit disappears.
- 1 12. (currently amended) The system of claim 1, in which dynamic view-
- 2 dependent images of an environment are displayed such that a display
- 3 surface of the display unit disappears.
- 1 13. (original) The system of claim 11 or 12, in which the view-dependent
- 2 images of the environment are acquired by a plurality of cameras.
- 1 14. (original) The system of claim 1, in which each producer module is
- 2 connected to a subset of the plurality of video cameras.
- 1 15. (original) The system of claim 1, in which the plurality of video cameras
- 2 are in a regularly spaced linear and horizontal array.

- 1 16. (original) The system of claim 1, in which the plurality of video cameras
- 2 are arranged arbitrarily.
- 1 17. (original) The system of claim 1, in which an optical axis of each video
- 2 camera is perpendicular to a common plane, and the up vectors of the
- 3 plurality of video cameras are vertically aligned.
- 1 18. (original) The system of claim 1, in which the viewing parameters
- 2 include intrinsic and extrinsic parameters of the video cameras.
- 1 19. (original) The system of claim 1, further comprising:
- 2 means for selecting a subset of the plurality of cameras for acquiring a
- 3 subset of videos.
- 1 20. (original) The system of claim 1, in which each video is compressed
- 2 individually and temporally.
- 1 21. (original) The system of claim 1, in which the viewing parameters
- 2 include a position, orientation, field-of-view, and focal plane, of each video
- 3 camera.
- 1 22. (currently amended) The system of claim 1, in which the controller
- determines, for each output pixel o(x, y) o(u, v) in the output video, a view
- 3 number v and a position of each source pixel s(v, x, y) in the decompressed
- 4 videos that contributes to the output pixel in the output video.

- 1 23. (original) The system of claim 22, in which the output pixel is a linear
- 2 combination of k source pixels according to

3
$$o(u,v) = \sum_{i=0}^{k} w_i s(v,x,y),$$

- 4 where blending weights w_i are predetermined by the controller based on the
- 5 viewing parameters.
- 1 24. (original) The system of claim 22, in which a block of the source pixels
- 2 contribute to each output pixel.
- 1 25. (original) The system of claim 1, in which the three-dimensional display
- 2 unit includes a display-side lenticular sheet, a viewer-side lenticular sheet, a
- diffuser, and substrate between each lenticular sheets and the diffuser.
- 1 26. (original) The system of claim 1, in which the three-dimensional display
- 2 unit includes a display-side lenticular sheet, a reflector, and a substrate
- 3 between the lenticular sheets and the reflector.
- 1 27. (currently amended) The system of claim 1, in which an arrangement of
- 2 the cameras and an arrangement of the display units, with respect to the
- 3 display unit, are substantially identical, and the number of cameras and the
- 4 <u>number of display units is greater than two.</u>
- 1 28. (currently amended) The system of claim 1, in which the plurality of
- 2 cameras acquire high-dynamic range videos the video of high dynamic light-
- 3 <u>fields</u>.

- 1 29. (currently amended) The system of claim 1, in which the display units
- 2 display high-dynamic range images of the output videos as high dynamic
- 3 <u>light-fields</u>.
 - 30. (canceled)
 - 31. (canceled)